

PRODUCT DATASHEET

Lexan™ Thermoclear™ Sheet

5X Structure in 16-32mm

DESCRIPTION

Lexan™ Thermoclear™ 5X structure sheets are members of the Lexan Thermoclear sheet product portfolio of high quality, multi-wall polycarbonate glazing sheets extruded from Lexan resin. The complete range offers remarkable impact strength, high light transmission, light weight, long term weather resistance and, due to the multi-wall construction, outstanding thermal insulation properties and is 2 sides UV protected. Lexan Thermoclear Plus 2UV sheet grades are available in Clear (112), Opal White (WH7A092X) & Solar Control IR Green (GN8B038T)

PRODUCT AVAILABILITY

SABIC Grade name	Standard Widths (mm)	Available lengths (mm)	(sheets/pallet) **
LT2UV165X27	980-1250-2100	3000-13000	25
LT2UV205X32	980-1250-2100	3000-13000	20
LT2UV255X34	980-1250-2100	3000-13000	20
LT2UV325X38	980-1250-2100	3000-13000	20

** please check our latest product guide for MOQ & Stock (MTI) items

TYPICAL PROPERTY VALUES

Grade	(mm)	Structure	weight (kg/m ²)	^ U value (W/m ² K)	Rib Distance (mm)
LT2UV165X27	16	5 wall X structure	2.70	1.88	20.00
LT2UV205X32	20	5 wall X structure	3.20	1.69	20.00
LT2UV255X34	25	5 wall X structure	3.40	1.51	20.00
LT2UV325X38	32	5 wall X structure	3.80	1.32	20.00

^ U-values based on SABIC calculated values according ISO 10077

LIGHT TRANSMISSION STANDARD COLORS

Grade	# LT 112 (%)	LT WH7A092X (%)	LT IR Green (%)
LT2UV165X27	59	51	42
LT2UV205X32	58	50	
LT2UV255X34	57	49	38
LT2UV325X38	55	48	36

Light transmission measurements acc. ISO 9050

PRODUCT DATASHEET


Lexan™ Thermoclear™ Sheet

5X Structure in 16-32mm

COLD CURVED GLAZING


Lexan Thermoclear sheet can be successfully cold curved over curved support glazing profiles, to suit many glazing applications, e.g. domes, roof-lights, etc. Providing the radius is not below the minimum recommended value of 2400mm, then the introduced stress by cold-curving will not have any adverse effect upon the mechanical performance of the sheet. Sheets must always be bent longitudinally, never across the width of the sheet. Sheet length needs to be greater than the sheet width to facilitate curvature; in practice, a ratio of 1:2 or less is never contemplated because of the practicalities of installation geometry.

Grade	Min. bending radius (mm) 150X gauge
LT2UV165X27	2400
LT2UV205X32	3000
LT2UV255X34	3750
LT2UV325X38	N/A




STRUCTURES & NOMENCLATURES

165X27 structure



205X32 structure




PRODUCT DATASHEET

Lexan™ Thermoclear™ Sheet


5X Structure in 16-32mm

STRUCTURES & NOMENCLATURES (continued)

255X34 structure



325X38 structure



PRODUCT DATASHEET

Lexan™ Thermoclear™ Sheet

5X Structure in 16-32mm

COATING AVAILABILITY

Lexan Thermoclear 2UV plus sheet:

Lexan Thermoclear 2UV plus sheet is the standard coating applied to both sides of the SABIC multiwall sheet and gives the product an excellent UV weathering performance.

Lexan Thermoclear SunXP sheet:

Lexan Thermoclear SunXP sheet is a coating which even enhances the weathering performance to the extent that SABIC offers a fifteen year written limited warranty with this product.

Lexan Thermoclear Solar Control IR (SCIR):

Lexan Thermoclear Solar control IR reduces significantly the solar transmission coming from the sun while simultaneously offering high levels of light transmission.

Lexan Thermoclear Solar Control:

Lexan Thermoclear solar control, the interior surface side will have a full Solar Control print lowering the solar transmittance coming from the sun light.

Lexan Thermoclear Venetian:

Lexan Thermoclear Venetian, the interior surface side will have Venetian printed stripes as an aesthetic view of the product.

SOLAR TRANSMISSION

Lexan Thermoclear sheet is essential opaque to all wavelengths below 385 nanometers. This useful shielding property can prevent discoloration of sensitive materials placed under or behind. Solar heat gain within a building is caused by heat input from radiation emitted from the sun. Sunlight entering the building heats the air both directly and through absorption by the framework, furniture, etc. and is released as infrared energy. In combination with the insulation properties of Lexan Thermoclear sheet, this prevents heat escaping faster than it is created causing a temperature increase, the so-called 'greenhouse effect'. The temperature can be controlled by venting, often in combination with special tinted opal white or Lexan Thermoclear SC IR which contains a proprietary additive which selectively absorbs the near infrared region of the light. Lexan Thermoclear is therefore available in many different colors or with IR additives, which both cuts down the brightness of sunlight to a pleasing level and reduces heat buildup inside the building. Calculations for solar heat input through glazing are normally based on data published in 'The Institution of Heating and Ventilating Engineers Guide Book'. These calculations are based on clear glass and correction factors or shading coefficients are then applied when alternative glazing materials are used.

UV RESISTANCE

The complete Lexan Thermoclear sheet range features a proprietary both sides surface treatment designed to protect the sheet against the degrading effects of ultra-violet radiation in natural sunlight. Both sides UV protected surfaces offers advantage in economically cutting the sheet in desired shapes, and installation mistakes are minimized since both sheet surfaces may be faced outwards.

WARRANTY

SABIC Innovative Plastics offers a Ten (10) Year Limited Written Warranty on Lexan Thermoclear sheet covering discoloration, loss of light transmission and loss of strength due weathering. See warranty for exact details.

PRODUCT DATASHEET

Lexan™ Thermoclear™ Sheet

5X Structure in 16-32mm

FIRE TEST PERFORMANCE

Lexan Thermoclear sheet has good fire performance against many national fire codes dependent on thickness and color; please check with the local sales office for details.

IMPACT STRENGTH

Lexan Thermoclear sheet has outstanding impact performance over a wide temperature range, -40°C to +120°C, and also after prolonged outdoor exposure. As a roof glazing material Lexan Thermoclear 2UV sheet is subjected to the extremes of weather; storms, hail stones, wind, snowfalls and ice formation. Under these conditions, the product is virtually unbreakable and is able to accommodate the subsequent temperature change to sunny conditions without breaking or buckling. Please refer to the warranty for details.

Americas

Headquarters

SABIC Innovative Plastics
One Plastics Avenue
Pittsfield, MA 01201
USA
T +1-413-448-7125
Toll-free: 1-800-323-3783
F +1 (888) 443-2033
sfscustomerservice@sabic-ip.com

European

Headquarters

SABIC Innovative Plastics
Plasticslaan 1
4612 PX
Bergen op Zoom
The Netherlands
T +31 164 293684
F +31 164 293272
Sfs.info@sabic-ip.com

Pacific

Headquarters

SABIC Innovative Plastics
Specialty Film & Sheet
1266 Nanjing Road (W)
16th Floor, Plaza 66
200040 Shanghai
China
T +86 21 62881088 ext. 6733
F +86 21 6288 0818

E-mail

sfscustomerservice@sabic-ip.com



* Trademark of SABIC Innovative Plastics IP BV

THE MATERIALS, PRODUCTS AND SERVICES OF SABIC INNOVATIVE PLASTICS HOLDING BV, ITS SUBSIDIARIES AND AFFILIATES ("SELLER"), ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH CAN BE FOUND AT <http://www.sabic-ip.com> AND ARE AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION OR RECOMMENDATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SELLER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING SELLER'S PRODUCTS, SERVICES OR RECOMMENDATIONS. EXCEPT AS PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user is responsible for making its own determination as to the suitability of Seller's products, services or recommendations for the user's particular use through appropriate end-use testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed by Seller. No statement by Seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Seller or as a recommendation for the use of such product, service or design in a manner that infringes any patent or other intellectual property right. LEXAN and THERMOCLEAR are trademarks of SABIC.

sabic-ip.com/sfs