

Product Handling Information Sheet

Polystone® Safe-Tec C

1. Company

Name/Address: Röchling Engineering Plastics KG

Röchlingstr. 1

D-49733 Haren/Germany

Tel.: +49 5934 701-0, Fax -300 info@roechling-plastics.com

www.roechling.com

2. Product details

Product/Article: Technical semi-finished product or machined part

Abbreviated terms: PP-HD / PE 300

Material characterisation: Semi crystalline plastic

Main components: Polyethylene, Stabiliser, Additives

Components subject to labelling: None Classification according to REACh: Article

Notes: -

3. Product characteristics

Form/State: Firm

Colour: Natural or coloured
Odour: Nearly odourless

Density: $0.93 - 0.98 \text{ g/cm}^3 \text{ (ISO } 1183)$

Melting range: $100^{\circ}\text{C} - 140^{\circ}\text{C} \text{ (DSC)}$

Glass transition temperature: -

Thermal decomposition: $> 390^{\circ}\text{C}$ Flash point: $\approx 340^{\circ}\text{C}$ Ignition temperature: $> 350^{\circ}\text{C}$

Notes: -

Creation date: 06.03.2009
Revision date: 12.07.2011
Print date: 19.07.2011

Index: 0 Page: 1 of 3



Product Handling Information Sheet

Polystone® Safe-Tec C

4. Danger warnings

Special risks for mankind and the

environment:

None

Notes: -

5. Handling and Storage

Handling: Product can be worked with commercially machines

and tools.

Before machining the product should have room temperature and/or to be stored for min. 24h under

normal climatic conditions

Storage: Horizontally, dry, protected against frost and climatic

influences

Safety measures: -

Notes: -

6. Transport

Transport: Non dangerous goods according to the transport

regulations

Secure against slipping

Notes: -

7. Fire – fighting measures

Suitable extinguishing agents: Water, foam, carbon dioxide (CO₂), dry powder

extinguishing agents

Potential combustion products: CO, CO₂

Necessary protection equipment: Complete protection equipment for fire-brigade

Use self-contained air respirators during strong smoke

and steam development

Notes: Molten product has to be cooled with water. Fire

residues must be collected and disposed of according

to the local instructions

Creation date: 06.03.2009
Revision date: 12.07.2011
Print date: 19.07.2011

Index: 0 Page: 2 of 3



Product Handling Information Sheet

Polystone® Safe-Tec C

8. Disposal references

Recyclability: Check possibility of recycling

EC Waste Catalogue: The product is classified in accordance with the

European-Waste Catalogue (EWC) as "Not

dangerous"

EC Waste Code: 120105 Plastics shavings and turnings

200139 Plastics of Separately collected fractions

Waste removal: Has to be conveyed to a suitable dumping site or

combustion plant in accordance with local regulations

Notes: -

9. References to marking, guidelines and regulations

Marking in accordance with

EEC-guidelines:

No labelling required

Other guidelines:

Notes: -

10. Information about REACh

In accordance with the EU directive 1907/2006/EC (REACh), article 3, no. 3, our products are clearly defined as articles not subject to registration.

The European directive regarding chemicals no. 1907/2006 (REACh) enforced on 1st June 2007 stipulates Material Safety Data Sheets (MSDS) only for dangerous substances and preparations. Our products do not fall under this scope of REACh.

11. Other information

The information in this document are based on our today's knowledge and represent no affirmation of characteristics. Existing laws and regulations are to be observed by the user of our product within his own responsibility.

Creation date: 06.03.2009
Revision date: 12.07.2011
Print date: 19.07.2011

Index: 0 Page: 3 of 3