

Rund, kvadratisk, heksagonal og rektangulær stang i henhold til EN 755-2

| Legering | Tilstand | Dimensjon | | Strekfasthet | | Flytegrense | | Forlengelse | | Hardhet |
|----------|---|-----------|-------------------|--------------|------|-------------|------|-------------|---------|--------------|
| | | Dia | NV/T ¹ | Rm MPa | | Rp 0,2 MPa | | A % | A50mm % | HBW |
| | | | | min. | max. | min. | max. | min. | min. | Typisk verdi |
| 2007 | T4,T4510, T4511 | ≤ 80 | ≤ 80 | 370 | - | 250 | - | 8 | 6 | 95 |
| | | 81-200 | 81-200 | 340 | - | 220 | - | 8 | - | |
| | | 201-250 | 201-250 | 330 | - | 210 | - | 7 | - | |
| 2011 | T4 T6 | ≤ 200 | ≤ 60 | 275 | - | 125 | - | 14 | 12 | 95 |
| | | ≤ 75 | ≤ 60 | 310 | - | 230 | - | 8 | 6 | 110 |
| | | 76-200 | - | 295 | - | 195 | - | 6 | - | |
| 2024 | O, H111 T3, T3510, T3511 T8, T8510, T8511 | ≤ 200 | ≤ 200 | - | 250 | - | 150 | 12 | 10 | 47 |
| | | ≤ 50 | ≤ 50 | 450 | - | 310 | - | 8 | 6 | 120 |
| | | 51-100 | 51-100 | 440 | - | 300 | - | 8 | - | |
| | | 101-200 | 101-200 | 420 | - | 280 | - | 8 | - | |
| | | 201-250 | 201-250 | 400 | - | 270 | - | 8 | - | |
| ≤ 150 | ≤ 150 | 455 | - | 380 | - | 5 | 4 | 130 | | |
| 5083 | F O, H111 H112 | ≤ 200 | ≤ 200 | 270 | - | 110 | - | 12 | 10 | 70 |
| | | 201-250 | 201-250 | 260 | - | 100 | - | 12 | - | |
| | | ≤ 200 | ≤ 200 | 270 | - | 110 | - | 12 | 10 | 70 |
| | | ≤ 200 | ≤ 200 | 270 | - | 125 | - | 12 | 10 | 70 |
| 6026 | T6 T8 T9 | ≤ 80 | ≤ 80 | 370 | - | 300 | - | 8 | 6 | 95 |
| | | ≤ 80 | ≤ 60 | 345 | - | 315 | - | 4 | 3 | 95 |
| | | ≤ 80 | ≤ 60 | 360 | - | 330 | - | 4 | 3 | 95 |
| 6060 | T4 T5 T6 T64 T66 | ≤ 150 | ≤ 150 | 120 | - | 60 | - | 16 | 14 | 50 |
| | | ≤ 150 | ≤ 150 | 160 | - | 120 | - | 8 | 6 | 60 |
| | | ≤ 150 | ≤ 150 | 190 | - | 150 | - | 8 | 6 | 70 |
| | | ≤ 50 | ≤ 50 | 180 | - | 120 | - | 12 | 10 | 60 |
| | | ≤ 150 | ≤ 150 | 215 | - | 160 | - | 8 | 6 | 75 |
| 6061 | O, H111 T4 T6 | ≤ 200 | ≤ 200 | - | 150 | - | 110 | 16 | 14 | 30 |
| | | ≤ 200 | ≤ 200 | 180 | - | 110 | - | 15 | 13 | 65 |
| | | ≤ 200 | ≤ 200 | 260 | - | 240 | - | 8 | 6 | 95 |
| 6082 | O, H111 T4 T6 | ≤ 200 | ≤ 200 | - | 160 | - | 110 | 14 | 12 | 35 |
| | | ≤ 200 | ≤ 200 | 205 | - | 110 | - | 14 | 12 | 70 |
| | | ≤ 20 | ≤ 20 | 295 | - | 250 | - | 8 | 6 | 95 |
| | | 21-150 | 21-150 | 310 | - | 260 | - | 8 | - | |
| | | 151-200 | 151-200 | 280 | - | 240 | - | 6 | - | |
| 201-250 | 201-250 | 270 | - | 200 | - | 6 | - | | | |
| 7075 | O, H111 T6, T6510, T6511 T73, T73510, T73511 | ≤ 200 | ≤ 200 | - | 275 | - | 165 | 10 | 8 | 60 |
| | | ≤ 25 | ≤ 25 | 540 | - | 480 | - | 7 | 5 | 150 |
| | | 26-100 | 26-100 | 560 | - | 500 | - | 7 | - | |
| | | 101-150 | 101-150 | 530 | - | 470 | - | 6 | - | |
| | | 151-200 | 151-200 | 470 | - | 400 | - | 5 | - | |
| | | ≤ 25 | ≤ 25 | 485 | - | 420 | - | 7 | 5 | 135 |
| | | 26-75 | 26-75 | 475 | - | 405 | - | 7 | - | |
| | | 76-100 | 76-100 | 470 | - | 390 | - | 6 | - | |
| 101-150 | 101-150 | 440 | - | 360 | - | 6 | - | | | |

¹ NV = Nøkkelvidde for kvadratisk og heksagonal stang. T = Tykkelse for rektangulær stang.